

# UNITRONIC® LiYY

Data transmission cable with colour code acc. to DIN 47100



**Info**

- The classic for multi-functional use

**Benefits**

- Space-saving installation due to small cable diameters
- Multifunctional application possibilities
- Depending on the quantity, the outer sheath can also be produced in other colours to match your application needs

**Application range**

- UNITRONIC® LiYY is also used as a control and signal cable in electronics of computer systems, electronic control equipment, office machines, balances, etc.
- Dry or damp rooms
- Occasional flexing

**Product features**

- Despite the large number of cores, LiYY data cables have small outer diameters
- Flame-retardant according IEC 60332-1-2

**Norm references / Approvals**

- Based on VDE 0812

**Product make-up**

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of PVC
- Outer sheath made of PVC  
Outer sheath colour: pebble grey (RAL 7032)

**Technical data**

- Core identification code**  
DIN 47100 without colour repetition, refer to Appendix T9
- Mutual capacitance**  
Approx. 120 nF/km
- Peak operating voltage**  
(not for power applications)  
at 0.14 mm<sup>2</sup>: 350 V  
at ≥ 0.25 mm<sup>2</sup>: 500 V
- Specific insulation resistance**  
> 20 GOhm x cm
- Inductivity**  
approx. 0.65 mH/km
- Conductor stranding**  
Stranded, fine-wire  
0.34 mm<sup>2</sup>: 7-wire
- Minimum bending radius**  
Occasional flexing: 10 x outer diameter  
Fixed installation: 4 x outer diameter
- Test voltage**  
At 0.14 mm<sup>2</sup>: 1200 V  
≥ 0.25 mm<sup>2</sup>: 1500 V
- Temperature range**  
Occasional flexing: -5°C to +70°C  
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>UNITRONIC® LiYY</b>				
0028202	2 x 0.14	3.2	2.7	13.2
0028203	3 x 0.14	3.4	4.0	16
0028204	4 x 0.14	3.6	5.4	18.9
0028205	5 x 0.14	3.9	6.7	22.2
0028207	7 x 0.14	4.2	9.4	28.4
0028208	8 x 0.14	4.9	10.2	35.2
0028210	10 x 0.14	5.2	13.5	41.2
0028212	12 x 0.14	5.6	16.2	48.4
0028214	14 x 0.14	5.8	18.9	52.9
0028216	16 x 0.14	6.1	21.6	59.1
0028220	20 x 0.14	7.0	27.0	70.8
0028225	25 x 0.14	7.8	33.6	87.2
0028236	36 x 0.14	8.6	48.6	126.8
0028237	37 x 0.14	8.9	49.7	118
0028240	40 x 0.14	9.3	54.0	139.1
0028250	50 x 0.14	10.4	67.5	170.9
0028256	56 x 0.14	10.7	78.4	187
0028302	2 x 0.25	3.8	4.8	18
0028303	3 x 0.25	4.0	7.2	22
0028304	4 x 0.25	4.3	9.6	26.2
0028305	5 x 0.25	4.7	12.0	31
0028306	6 x 0.25	5.1	14.4	39
0028307	7 x 0.25	5.1	16.8	42
0028308	8 x 0.25	6.2	19.2	49.2
0028310	10 x 0.25	6.8	24.0	58
0028312	12 x 0.25	7.0	28.8	67
0028314	14 x 0.25	7.3	33.6	75.3
0028316	16 x 0.25	7.7	38.4	84.3
0028318	18 x 0.25	8.1	43.2	93
0028320	20 x 0.25	8.6	48.0	102
0028325	25 x 0.25	9.6	60.0	134
0028330	30 x 0.25	10.3	72.0	155
0028332	32 x 0.25	10.7	76.8	164
0028336	36 x 0.25	11.1	86.4	182.2
0028337	37 x 0.25	11.4	88.8	185
0028340	40 x 0.25	12.0	96.1	200
0028350	50 x 0.25	12.9	120.0	257.1

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0028402	2 x 0.34	4.2	6.6	25
0028403	3 x 0.34	4.4	9.9	31
0028404	4 x 0.34	4.8	13.1	43.2
0028405	5 x 0.34	5.5	16.5	53.8
0028406	6 x 0.34	5.9	19.6	55
0028407	7 x 0.34	5.9	22.8	62
0028408	8 x 0.34	7.1	26.1	73.1
0028410	10 x 0.34	7.6	32.6	82
0028412	12 x 0.34	7.8	39.1	102
0028414	14 x 0.34	8.2	45.7	109
0028416	16 x 0.34	8.7	52.0	127
0028420	20 x 0.34	9.6	65.2	159.3
0028421	21 x 0.34	10.4	68.6	167
0028425	25 x 0.34	11.2	81.6	190
0028430	30 x 0.34	11.6	98.0	226
0028436	36 x 0.34	12.5	118.0	284
0028440	40 x 0.34	13.5	131.0	317
0028450	50 x 0.34	15.0	163.0	407
0028502	2 x 0.50	4.7	9.6	40
0028503	3 x 0.50	5.0	14.4	47
0028504	4 x 0.50	5.6	19.2	56
0028505	5 x 0.50	6.1	24.0	65
0028507	7 x 0.50	6.9	33.6	82
0028508	8 x 0.50	8.0	38.4	90
0028510	10 x 0.50	8.6	48.0	117
0028512	12 x 0.50	8.9	58.0	133
0028516	16 x 0.50	10.2	77.0	170
0028520	20 x 0.50	11.4	96.0	214
0028525	25 x 0.50	12.7	120.0	265
0028530	30 x 0.50	13.2	144.0	304
0028540	40 x 0.50	15.8	192.0	392
0028602	2 x 0.75	5.1	14.4	48
0028603	3 x 0.75	5.6	21.6	57
0028604	4 x 0.75	6.1	28.8	69
0028605	5 x 0.75	6.9	36.0	78
0028607	7 x 0.75	7.5	50.0	112
0028608	8 x 0.75	8.7	58.0	126
0028610	10 x 0.75	9.4	72.0	149
0028612	12 x 0.75	10.1	86.0	176
0028616	16 x 0.75	11.2	115.0	218
0028620	20 x 0.75	12.4	144.0	274
0028625	25 x 0.75	14.0	180.0	285
0028702	2 x 1.00	5.6	19.2	55
0028703	3 x 1.00	5.9	29.0	70
0028704	4 x 1.00	6.4	38.4	79
0028705	5 x 1.00	7.3	48.0	98
0028802	2 x 1.50	6.2	29.0	74
0028803	3 x 1.50	6.8	43.0	89
0028804	4 x 1.50	7.4	58.0	105

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

**Similar products**

- UNITRONIC® LiYY (TP) refer to page 250
- UNITRONIC® LiYY A refer to page 266

**Accessories**

- SKINTOP® ST-M refer to page 654
- STAR STRIP stripping tool refer to page 910
- SENSOR STRIP stripping tool refer to page 912