



**SILVYN® KLICK 90° PG**



**Benefits**

- 90° elbow allows easy installation
- Fast assembly
- Easy to disassemble
- High-tensile
- High sealing performance

**Application range**

- In combination with protective conduit:
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- For applications with limited space
- Rotating applications

**Norm references / Approvals**

- UL FILENUMBER E308201

**Product make-up**

- PG connection thread
- 90° elbow
- Body with inner sealing
- Upper part with snap-in sleeve

**Suitable conduits**

- SILVYN® RILL PA 6 Page 789
- SILVYN® RILL PA 12 Page 790

**Technical data**

<b>RAL</b>	<b>Colour delivered</b> Grey (RAL 7001) Black (RAL 9005), UV-resistant
<b>Material</b>	PA6
<b>IP</b>	<b>Protection rating</b> IP 68 IP 69K according to DIN 40050 T.9
<b>Temperature range</b>	-40 °C to +115 °C

Article number	Article designation	Suitable for SILVYN® RILL	For conduit with outer Ø (mm)	Thread length (mm)	Clear opening (mm)	Pieces / PU
<b>SILVYN® KLICK 90° PG grey</b>						
61801020	9	9	13	10	12,0	50
61801030	11	11	15,8	10	15,5	50
56000100	13,5	13,5	18,5	11	13,5	50
61801040	16	16	21,2	12	18,0	50
61801050	21	21	28,5	12	24,0	25
61801060	29	29	34,5	12	32,0	10
61801061	36	36	42,5	14	36,5	10
61801062	48	48	54,5	14	48,5	5
<b>SILVYN® KLICK 90° PG black</b>						
61801025	9	9	13	10	12,0	50
61801035	11	11	15,8	10	15,5	50
56000105	13,5	13,5	18,5	11	13,5	50
61801045	16	16	21,2	12	18,0	50
61801055	21	21	28,5	12	24,0	25
61801065	29	29	34,5	12	32,0	10

Photographs are not to scale and do not represent detailed images of the respective products.