



SILVYN® KLIICK-GM



Benefits

- Fast assembly
- Easy to disassemble
- High-tensile
- High sealing performance
- Can be rotated

Application range

- In combination with protective conduit:
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- Robot-building
- Rotating applications

Norm references / Approvals

- UL FILENUMBER E308201

Product make-up

- Metric connection thread
- Body with inner sealing
- Upper part with snap-in sleeve

Suitable conduits

- SILVYN® RILL PA 6 Page 789
- SILVYN® RILL PA 12 Page 790

Technical data

RAL	Colour delivered Grey (RAL 7001) Black (RAL 9005), UV-resistant
Material	PA6
IP	Protection rating IP 68 IP 69K according to DIN 40050 T.9
Temperature range	-40 °C to +115 °C

Article number	Connection thread M	Hole Ø (mm)	For conduit with outer Ø (mm)	Thread length, D (mm)	SW (mm)	Suitable for SILVYN® RILL	Pieces / PU
SILVYN® KLIICK-GM grey							
55501000	10 x 1.0	6.5	10.0	12.0	17.0	6,5 x 10,0	50
55501010	12 x 1.5	8.0	13.0	12.0	20.0	10 x 13,0	50
55501020	16 x 1.5/1	10.0	13.0	12.0	20.0	10 x 13,0	50
55501030	16 x 1.5/2	12.0	15.8	12.0	23.0	12 x 15,8	50
55501040	20 x 1.5/1	12.0	15.8	13.0	23.0	12 x 15,8	50
55501050	20 x 1.5/2	16.0	21.2	13.0	29.5	16,5 x 21,2	50
55501060	25 x 1.5	20.5	28.5	13.0	37.0	23 x 28,5	25
55501070	32 x 1.5	27.5	34.5	15.0	44.0	29 x 34,5	25
55501080	40 x 1.5	35.0	42.5	15.0	51.5	36 x 42,5	25
55501090	50 x 1.5	45.0	54.5	15.3	65.5	48 x 54,5	10
55500990	63 x 1.5	48.0	54.5	16.0	59.0	48 x 54,5	10
SILVYN® KLIICK-GM black							
55501005	10 x 1.0	6.5	10.0	12.0	17.0	6,5 x 10,0	50
55501015	12 x 1.5	8.0	13.0	12.0	20.0	10 x 13,0	50
55501025	16 x 1.5/1	10.0	13.0	12.0	20.0	10 x 13,0	50
55501035	16 x 1.5/2	12.0	15.8	12.0	23.0	12 x 15,8	50
55501045	20 x 1.5/1	12.0	15.8	13.0	23.0	12 x 15,8	50
55501055	20 x 1.5/2	16.0	21.2	13.0	29.5	16,5 x 21,2	50
55501065	25 x 1.5	20.5	28.5	13.0	37.0	23 x 28,5	25
55501075	32 x 1.5	27.5	34.5	15.0	44.0	29 x 34,5	25
55501085	40 x 1.5	35.0	42.5	15.0	51.5	36 x 42,5	25
55501095	50 x 1.5	45.0	54.5	15.3	65.5	48 x 54,5	10
55500995	63 x 1.5	48.0	54.5	16.0	59.0	48 x 54,5	10

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- SILVYN® KLIICK GPZ-M refer to page 793