


Conveyor technology

For push-button control units



## ÖLFLEX® CRANE 2S

Flexible at cold temperatures, PVC cables with external steel supporting elements



**Info**

- Double tensile strength safety
- Teach pad cable

**Benefits**

- Two steel support elements that are integrated into the outer sheath on opposite sides absorb the tensile forces during operation
- Tensile strength of 2100 N per supporting element

**Application range**

- For connecting movable control panels and consoles
- As a self-supporting shaft cable; in high rack systems
- Suitable for outdoor applications
- Do not use for lift applications!
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3

**Norm references / Approvals**

- Flame-retardant according IEC 60332-1-2
- Flexible at low temperatures

**Norm references / Approvals**

- Based on VDE 0250

**Product make-up**

- Strands of bare copper wires
- Special PVC-based core insulation
- Special textile wrapping to improve sliding movement between the sheath and cores
- Special PVC-based outer sheath
- Opposing, integrated steel supporting elements

**Technical data**

**Classification**  
ETIM 5.0 Class-ID: EC000104  
ETIM 5.0 Class-Description: Control cable

**Core identification code**  
Black with white numbers acc. to VDE 0293-1

**Specific insulation resistance**  
> 20 GOhm x cm

**Conductor stranding**  
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6

**Minimum bending radius**  
Flexible use: 20 x outer diameter

**Nominal voltage**  
U<sub>0</sub>/U: 300/500 V

**Test voltage**  
3000 V

**Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor

**Temperature range**  
Flexible use: -15°C to +70°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Cable Ø (mm)	Distance between strain wires (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® CRANE 2S</b>					
0027503	8 G 1.5	14.7	20	115.0	372.5
0027504	12 G 1.5	16.2	21	172.8	439
0027505	20 G 1.5	20.1	25	288.0	674

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
Photographs are not to scale and do not represent detailed images of the respective products.

**Accessories**

- EASY STRIP stripping and cutting tool refer to page 909

ÖLFLEX® UNITRONIC® ETHERLINE® HITRONIC® EPIC® SKINTOP® SILVYN® FLEXIMARK® ACCESSORIES APPENDIX