

Expanded ambient temperatures

Silicone cables (-50°C to +180°C)



ÖLFLEX® HEAT 180 SiHF

Silicone cables with extended temperature range



Info

- The classic for multi-functional use

Benefits

- Flexibility simplifies installation where space is limited
- Possesses insulating properties after combustion due to remaining SiO₂ ash on the conductor

Application range

- Areas with high ambient temperatures where insulating and sheath materials of conventional cables will embrittle after a short while
- Typical fields of application
 - Steel, ceramic and iron works
 - Bakery equipment and industrial furnaces
 - Electric motor industry
 - Sauna/solarium construction
 - Thermal and heating elements
 - Lighting technology
 - Ventilator engineering
 - Air-conditioning technology
 - Galvanisation technology

Product features

- Halogen-free and flame-retardant (IEC 60332-1-2)
- Resistant to a multitude of oils, alcohols, vegetable and animal fats and chemical substances

Product make-up

- Fine-wire, tinned-copper conductor
- Silicone-based core insulation
- Cores twisted in layers
- Silicone-based outer sheath, colour red-brown

Technical data



Classification

ETIM 5.0 Class-ID: EC001578
ETIM 5.0 Class-Description: Flexible cable



Core identification code

Colours according to VDE 0293-308, refer to Appendix T9
From 6 cores: black with white numbers



Specific insulation resistance

>200 GOhm x cm



Conductor stranding

Fine wire according to VDE 0295 Class 5 / IEC 60228 Class 5



Minimum bending radius

Occasional flexing: 15 x outer diameter
Fixed installation: 4 x outer diameter



Nominal voltage

U₀/U: 300/500 V



Test voltage

2000 V



Protective conductor

G = with GN-YE protective conductor
X = without protective conductor



Temperature range

-50 °C to +180 °C
(adequate ventilation required)

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 180 SiHF				
0046001	2 X 0.75	6.4	14.4	59
0046002	3 G 0.75	6.8	21.6	70
00460033	4 G 0.75	7.6	28.8	89
00460043	5 G 0.75	8.5	36.0	112
0046005	6 G 0.75	9.2	43.2	131
0046006	7 G 0.75	9.2	50.4	136
0046007	2 X 1	6.6	19.2	66
0046008	3 G 1	7.0	29.0	79
00460093	4 G 1	7.9	38.4	101
00460103	5 G 1	8.8	48.0	127
0046012	7 G 1	9.5	67.0	156
0046013	2 X 1.5	7.6	29.0	90
0046014	3 G 1.5	8.0	43.0	109
00460153	4 G 1.5	8.8	58.0	134
00460163	5 G 1.5	9.6	72.0	163
0046018	7 G 1.5	10.4	101.0	202
0046039	12 G 1.5	14.0	173.0	361
0046040	16 G 1.5	16.2	230.4	478
0046041	20 G 1.5	17.5	288.0	574

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0046042	24 G 1.5	19.8	345.6	720
0046019	2 X 2.5	8.8	48.0	128
0046020	3 G 2.5	9.7	72.0	167
00460213	4 G 2.5	10.6	96.0	206
00460223	5 G 2.5	11.6	120.0	251
0046024	7 G 2.5	12.6	168.0	313
0046025	2 X 4	10.8	76.8	196
0046026	3 G 4	11.5	115.0	241
00460273	4 G 4	12.6	154.0	300
00460283	5 G 4	14.0	192.0	374
0046030	7 G 4	15.6	269.0	486
0046031	2 X 6	12.4	116.0	268
0046032	3 G 6	13.2	173.0	333
00460333	4 G 6	14.7	230.0	425
00460343	5 G 6	16.6	288.0	538
0046036	7 G 6	18.6	403.0	705
00460373	4 G 10	19.4	384.0	707
00460453	5 G 10	21.6	480.0	878
00460383	4 G 16	21.4	614.0	1004

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® HEAT 180 H05SS-F EWKF refer to page 167
- ÖLFLEX® HEAT 180 EWKF refer to page 170