

Protection Devices

Miniature Circuit Breakers (MCBs)

C60H-DC

250Vdc per Pole
IEC/EN 60947-2

Exclusively designed to take care of all issues in DC installations to ensure complete Short circuit and Overload Protection

Key Features

- Widest Range - 0.5A to 63A
- Ensures no accidental contact with live part - Finger-proof IP-20 terminals
- Avoids false insertion of cables and loose termination: Pull up terminals:
- Operational Safety at the downstream - Suitability for Isolation
- Field fittable auxiliaries available for advanced protection & monitoring

Technical Data

Parameter	C60H-DC
No of Poles	1,2
Rated Voltage	250VDC (1P)
	500VDC (2P)
Terminal Capacity	Rigid upto 35 sqmm
	Flexible upto 25 sqmm
Impulse Withstand Voltage	6kV
Breaking Capacity	6kA
Energy limiting class	3
Operating Temperature	-25 to 70°C



MCB C60H-DC		Poles		References	
Rating (A)	1P	Curve C			
		1P	2P		
0.5	A9N61500		A9N61520		
1	A9N61501		A9N61521		
2	A9N61502		A9N61522		
3	A9N61503		A9N61523		
4	A9N61504		A9N61524		
5	A9N61505		A9N61525		
6	A9N61506		A9N61526		
10	A9N61508		A9N61528		
13	A9N61509		A9N61529		
15	A9N61510		A9N61530		
16	A9N61511		A9N61531		
20	A9N61512		A9N61532		
25	A9N61513		A9N61533		
30	A9N61514		A9N61534		
32	A9N61515		A9N61535		
40	A9N61517		A9N61537		
50	A9N61518		A9N61538		
63	A9N61519		A9N61539		
Module Width		1	2		

**Module width - 18mm/Module