



SILVYN® KLIICK GPZ-M



Benefits

- Fast assembly
- Easy to disassemble
- Additional cable strain relief
- Additional cable sealing

Application range

- In combination with protective conduit:
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- Robot-building
- Used in areas where cables and wires need to be provided with strain relief and additional sealing

Norm references / Approvals

- UL FILENUMBER E308201

Product make-up

- Metric connection thread
- Cable gland
- Body with inner sealing
- Upper part with snap-in sleeve

Suitable conduits

- SILVYN® RILL PA 6 Page 789
- SILVYN® RILL PA 12 Page 790

Technical data

RAL	Colour delivered Grey (RAL 7001) Black (RAL 9005), UV-resistant
Material	PA6
IP	Protection rating IP 68 IP 69K according to DIN 40050 T.9
Temperature range	-30°C to +100°C

Article number	Article designation	Hole Ø (mm)	Clamping range (mm)	Thread length, D (mm)	For conduit with outer Ø (mm)	SW (mm)	Suitable for SILVYN® RILL	Pieces / PU
SILVYN® KLIICK GPZ-M grey								
55500800	12 x 1,5	7,0	4,0 - 6,5	8,0	10,0	16,0	7	20
55500810	16 x 1,5	8,0	5,0 - 9,5	8,0	13,0	18,0	9	20
55500820	20 x 1,5	10,0	8,0 - 12,0	8,0	15,8	21,0	11	20
55500830	25 x 1,5	12,0	11,0 - 16,0	8,0	21,2	27,0	16	10
55500840	32 x 1,5	18,0	15,0 - 21,0	11,0	28,5	34,0	21	10
55500850	40 x 1,5	25,0	16,0 - 26,0	12,0	34,5	40,0	29	10
55500860	50 x 1,5	32,0	27,0 - 35,0	13,0	42,5	49,0	36	10
55500870	63 x 1,5	44,0	32,0 - 42,0	14,0	54,5	60,0	48	10
SILVYN® KLIICK GPZ-M black								
55500805	12 x 1,5	7,0	4,0 - 6,5	8,0	10,0	16,0	7	20
55500815	16 x 1,5	8,0	5,0 - 9,5	8,0	13,0	18,0	9	20
55500825	20 x 1,5	10,0	8,0 - 12,0	8,0	15,8	21,0	11	20
55500835	25 x 1,5	12,0	11,0 - 16,0	8,0	21,2	27,0	16	10
55500845	32 x 1,5	18,0	15,0 - 21,0	11,0	28,5	34,0	21	10
55500855	40 x 1,5	25,0	16,0 - 26,0	12,0	34,5	40,0	29	10
55500865	50 x 1,5	32,0	27,0 - 35,0	13,0	42,5	49,0	36	10
55500875	63 x 1,5	44,0	32,0 - 42,0	14,0	54,5	60,0	48	10

Photographs are not to scale and do not represent detailed images of the respective products.