



Info

- Good chemical resistance
- Wide temperature application range
- Thin, light and robust

Info

- EMC compliant copper screening

ÖLFLEX® HEAT 205 MC

Fluorinated ethylene propylene cables for harsh applications



ÖLFLEX® HEAT 205 PTFE/FEP

4-cored version with PTFE insulation and special core identity code



Benefits

- Space and weight-saving installations due to small cable diameters
- Resistant to contact with mostly all highly aggressive chemical media
- Low outgassing behaviour

Application range

- Conventional cables are not designed for use in environments with very high operating temperatures, heavy usage of chemical agents, or tight spaces
- Typical fields of application
 - Industrial furnace construction
 - Foundries
 - Chemical industry
 - Power plant engineering
 - Paint shop line technology
 - Heating elements
 - Polymer processing
 - Wind turbine engineering

Norm references / Approvals

- ÖLFLEX® HEAT 205 made of FEP
 - Outstanding resistance against acids, solvents, lacquers, petrol, oils and many other chemical media
 - Difficult to inflame
 - High dielectric strength and high abrasion resistance
 - Low water absorption
 - Resistant to microbes
 - Adhesion free insulation materials
 - Weather and ozone resistant
 - Hydrophobic and dirt-repellent
 - High elongation and tear resistance
 - Resistant against hydraulic fluids

Product make-up

- **ÖLFLEX® HEAT 205 MC**
 - Fine-wire, tinned-copper conductor
 - FEP-based core insulation
 - Cores twisted together
 - FEP-based outer sheath, black
- **ÖLFLEX® HEAT 205 PTFE/FEP**
 - Fine-wire, tinned-copper conductor
 - PTFE-based core insulation
 - Cores twisted together
 - Tinned-copper braiding
 - Outer sheath: FEP-based, white

Technical data

- **Classification**
ETIM 5.0 Class-ID: EC001578
ETIM 5.0 Class-Description: Flexible cable
- **Core identification code**
ÖLFLEX® HEAT 205 MC
Up to 5 cores: colour-coded acc. to VDE 0293-308
From 7 cores: ÖLFLEX® colour-codes, refer to Appendix T7
ÖLFLEX® HEAT 205 PTFE/FEP
Blue, red, grey, black
- **Conductor stranding**
Fine wire acc. to VDE 0295, class 5 / IEC 60228 class 5 from 0.5 mm²
- **Minimum bending radius**
Occasional flexing: 15 x outer diameter
Fixed installation: 4 x outer diameter
- **Nominal voltage**
U₀/U: 300/500 V
- **Test voltage**
ÖLFLEX® HEAT 205 MC
2500 V
ÖLFLEX® HEAT 205 PTFE/FEP
C/C: 2500 V
C/S: 2000 V
- **Protective conductor**
G = with GN-YE protective conductor
X = without protective conductor
- **Temperature range**
Fixed installation: -100°C to +205°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 205 MC				
0091200	2 X 0.25	3.1	5.0	17.2
0091201	3 G 0.25	3.3	7.5	22.2
00912023	4 G 0.25	3.6	10.0	27.5
0091210	2 X 0.5	3.8	9.8	21.6
0091211	3 G 0.5	4.0	14.7	32.8
00912123	4 G 0.5	4.4	19.6	44.4
0091220	2 X 0.75	4.2	14.4	31.5
0091221	3 G 0.75	4.6	21.6	46.1
00912223	4 G 0.75	4.9	29.0	57.9
0091230	2 X 1	4.5	19.0	41.6
0091231	3 G 1	4.8	29.0	55.6

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
00912323	4 G 1	5.3	38.0	70
0091100	3 G 1.5	5.6	43.0	70
00911033	4 G 1.5	6.1	58.0	98
00911013	5 G 1.5	6.8	72.0	117
0091102	7 G 1.5	7.4	101.0	184
0091236	3 G 2.5	6.6	72.0	86
00912353	4 G 2.5	7.3	96.0	115
00912373	5 G 2.5	8.2	120.0	144
00912423	4 G 4	8.7	154.0	180
00912433	5 G 4	9.6	192.0	225
ÖLFLEX® HEAT 205 PTFE/FEP				
30016373	4 X 0.75	5.9	49.0	78

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

ÖLFLEX® HEAT 205 MC

- ÖLFLEX® HEAT 260 MC refer to page 174