


Expanded ambient temperatures

Silicone single cores (-50°C to +180°C)



ÖLFLEX® HEAT 180 SiF

Versatile stranded conductors with extended temperature range

Info

- Flexible fine-wire copper conductor

Application range

- Areas with high ambient temperatures where conventional core insulation materials will embrittle after a short while
- Typical fields of application
 - Control cabinet manufacturing
 - Appliances and apparatus engineering
 - Electric motor industry
 - Sauna/solarium construction
 - Thermal and heating elements
 - Lighting technology
 - Ventilator engineering
 - Air-conditioning technology
 - Furnace construction
 - Polymer processing
 - Generator and transformer manufacturing

Product features

- Halogen-free according to IEC 60754-1
- Resistant to a multitude of oils, alcohols, vegetable and animal fats and chemical substances

Product make-up

- Fine-wire, tinned-copper conductor
- Silicone-based insulation

Technical data

Classification
ETIM 5.0 Class-ID: EC000993
ETIM 5.0 Class-Description: Single core cable

Specific insulation resistance
>200 GOhm x cm

Conductor stranding
Fine wire acc. to VDE 0295, class 5 / IEC 60228 class 5 from 0.5 mm²

Minimum bending radius
Fixed installation: 6 x core diameter
One bend at end of core:
3 x cable diameter

Nominal voltage
U₀/U: 300/500 V

Test voltage
2000 V

Temperature range
-50 °C to +180 °C
(adequate ventilation required)
Short-term: +200°C

Conductor cross-section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)	brown	black	grey	blue	green/yellow	orange	white
0.25	1.9	2.4	5.4	0047003	0047001	0047106	0047002	0047000	0047009	0047105
0.5	2.1	4.8	9.0	0048003	0048001	0048106	0048002	0048000	0048009	0048105
0.75	2.4	7.2	12.0	0049003	0049001	0049106	0049002	0049000	0049009	0049105
1	2.5	9.6	15.0	0050003	0050001	0050106	0050002	0050000	0050009	0050105
1.5	2.8	14.4	20.0	0051003	0051001	0051106	0051002	0051000	0051009	0051105
2.5	3.4	24.0	32.0	0052003	0052001	0052106	0052002	0052000		0052105
4	4.2	38.0	50.0	0053003	0053001	0053106	0053002	0053000	0053009	0053105
6	5.0	58.0	73.0	0054003	0054001	0054106	0054002	0054000		0054105
10	6.6	96.0	118.0	0055003	0055001	0055106	0055002	0055000	0055009	
16	7.4	154.0	177.0		0056001	0056106	0056002	0056000		
25	9.2	240.0	277.0		0057001	0057106	0057002	0057000		
35	10.3	336.0	374.0		0058001		0058002	0058000		
50	12.2	480.0	530.0		0059001			0059000		
70	14.2	672.0	724.0		0060001		0060002	0060000		
95	16.6	912.0	982.0		0061001			0061000		0061105
120	18.0	1,152.0	1,219.0		0062001			0062000		
150	20.0	1,440.0	1,524.0		0063001					
185	22.5	1,776.0	1,915.0		0064001					

Conductor cross-section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)	green	yellow	violet	red	pink	beige
0.25	1.9	2.4	5.4	0047006	0047005	0047007	0047104	0047008	
0.5	2.1	4.8	9.0	0048006	0048005	0048007	0048104	0048008	
0.75	2.4	7.2	12.0	0049006	0049005	0049007	0049104	0049008	
1	2.5	9.6	15.0	0050006	0050005	0050007	0050104	0050008	0050004
1.5	2.8	14.4	20.0	0051006	0051005	0051007	0051104	0051008	
2.5	3.4	24.0	32.0	0052006	0052005	0052007	0052104		
4	4.2	38.0	50.0	0053006	0053005		0053104		
6	5.0	58.0	73.0	0054006	0054005		0054104		0054004
10	6.6	96.0	118.0				0055104		
16	7.4	154.0	177.0				0056104		
25	9.2	240.0	277.0				0057104		
35	10.3	336.0	374.0				0058104		
50	12.2	480.0	530.0				0059104		

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Also available on large spools and non-returnable drums.
 Photographs are not to scale and do not represent detailed images of the respective products.
 Article number index of core colours: 000 = green-yellow; 001 = black; 002 = blue; 003 = brown; 004 = beige; 005 = yellow; 006 = green; 007 = violet; 008 = pink; 009 = orange; 104 = red; 105 = white; 106 = grey
 Other colours are available upon request

ÖLFLEX®
 UNITRONIC®
 ETHERLINE®
 HITRONIC®
 EPIC®
 SKINTOP®
 SILVYN®
 FLEXIMARK®
 ACCESSORIES
 APPENDIX