

ÖLFLEX® CLASSIC 100 300/500 V

Colour-coded PVC control cable

Info

- CPR: Article number choice under www.lappkabel.com/cpr
- For nominal voltage U0/U: 450/750V or higher conductor cross-sections see ÖLFLEX® CLASSIC 100 450/750V



Benefits

- Space-saving installation due to small cable diameters
- High electrical performance due to 4 kV test voltage
- High flexibility due to short-twisted conductor layers

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
Power stations
- Dry or damp rooms that are subject to medium mechanical loads
- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)
- High-quality alternative to control cable types YSLY or YY

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- PVC outer sheath, grey (similar RAL 7001)

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC001578 ETIM 5.0/6.0 Class-Description: Flexible cable
	Core identification code Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: ÖLFLEX® colour code, refer to Appendix T7
	Conductor stranding Fine wire according to VDE 0295, class 5/IEC 60228 class 5
	Torsion movement in WTG TW-0 & TW-1, refer to Appendix T0
	Minimum bending radius Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
	Nominal voltage U0/U: 300/500 V
	Test voltage 4000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 300/500 V				
00100004	2 X 0.5	4.8	9.6	35
00100014	3 G 0.5	5.1	14.4	42
00101224	3 X 0.5	5.1	14.4	42
00100024	4 G 0.5	5.7	19.2	54
00101234	4 X 0.5	5.7	19.2	54
00100034	5 G 0.5	6.2	24	63
00101244	5 X 0.5	6.2	24	63
0010004	6 G 0.5	6.7	28.8	73
0010005	7 G 0.5	6.7	33.6	81
0010006	8 G 0.5	8.0	38.4	97
0010007	10 G 0.5	8.6	48	116
0010008	12 G 0.5	8.9	58	133
0010009	14 G 0.5	9.5	67	151
0010010	16 G 0.5	10.0	76	169
0010011	21 G 0.5	11.7	99	223
0010012	24 G 0.5	12.4	114	254
0010016	40 G 0.5	15.4	192	404
00100214	2 X 0.75	5.4	14.4	45
00100224	3 G 0.75	5.7	21.6	55
00101254	3 X 0.75	5.7	21.6	55
00100234	4 G 0.75	6.2	28.8	66
00101264	4 X 0.75	6.2	28.8	66

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
00100244	5 G 0.75	6.7	36	79
00101274	5 X 0.75	6.7	36	79
0010025	6 G 0.75	7.3	43.3	104
0010026	7 G 0.75	7.3	50.4	109
0010027	8 G 0.75	8.8	56	123
0010028	9 G 0.75	9.4	63	144
0010029	10 G 0.75	9.6	72	153
0010030	12 G 0.75	9.9	86.4	176
0010031	15 G 0.75	10.9	108	211
0010032	18 G 0.75	11.7	129.6	268
0010033	21 G 0.75	13.0	151	293
0010034	25 G 0.75	13.8	180	374
0010036	40 G 0.75	17.3	288	571
0010037	50 G 0.75	19.2	360	698
00100414	2 X 1.0	5.7	19.2	53
00100424	3 G 1.0	6.0	28.8	65
00102034	3 X 1.0	6.0	28.8	65
00100434	4 G 1.0	6.5	38.4	79
00102044	4 X 1.0	6.5	38.4	79
00100444	5 G 1.0	7.1	48	94
00102054	5 X 1.0	7.1	48	94
0010045	6 G 1.0	8.0	58	124
0010046	7 G 1.0	8.0	67	131

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0010047	8 G 1.0	9.5	77	146
0010049	10 G 1.0	10.2	96	183
0010050	12 G 1.0	10.5	115	215
0010052	16 G 1.0	11.8	154	282
0010053	18 G 1.0	12.7	173	315
0010054	20 G 1.0	13.4	192	350
0010056	25 G 1.0	14.7	240	449
00100634	2 X 1.5	6.3	28.8	68
00100644	3 G 1.5	6.7	43.2	84
00101284	3 X 1.5	6.7	43.2	84
00100654	4 G 1.5	7.2	57.6	104
00101294	4 X 1.5	7.2	57.6	104
00100664	5 G 1.5	8.1	72	128
00101304	5 X 1.5	8.1	72	128
0010068	7 G 1.5	8.9	101	166
0010069	8 G 1.5	10.6	115	205
0010071	12 G 1.5	12.0	173	307
0010072	14 G 1.5	12.7	202	349
0010074	18 G 1.5	14.4	259	465
0010076	25 G 1.5	16.9	360	655
1120800	2 X 2.5	7.5	48	100
1120801	3 G 2.5	8.1	72	132
1120802	4 G 2.5	8.9	96	163
1120803	5 G 2.5	10.0	120	200
1120804	7 G 2.5	11.1	168	267

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1120805	2 X 4	9.2	77	160
1120806	3 G 4	9.9	115.2	201
1120807	4 G 4	10.8	153.6	263
1120808	5 G 4	12.1	192	315
1120809	7 G 4	13.4	269	407
1120810	3 G 6	11.7	174	289
1120811	4 G 6	13.0	230	352
1120812	5 G 6	14.5	288	470
1120813	7 G 6	16.0	403	600
1120814	3 G 10	14.6	288	466
1120815	4 G 10	16.2	384	590
1120816	5 G 10	18.1	480	722
1120817	3 G 16	17.0	460.8	720
1120818	4 G 16	18.8	614.4	1067
1120819	5 G 16	21.2	768	1370
1120820	3 G 25	21.0	720	1250
1120821	4 G 25	23.5	960	1582
1120822	5 G 25	26.4	1200	1998
1120823	3 G 35	23.7	1008	1700
1120824	4 G 35	26.4	1344	2106
1120825	5 G 35	29.6	1680	2635
1120826	3 G 50	29.1	1440	2200
1120827	4 G 50	32.4	1920	2800
1120828	5 G 50	36.5	2400	3600

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Single lengths for sizes: ≥ 5G50 max. 500 m; ≥ 5G95 max. 400; ≥ 3G120 max. 500 m; ≥ 4G120 max. 300; ≥ 4G185 max. 250 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- UNITRONIC® 100 refer to page 276
- ÖLFLEX® CLASSIC 100 H refer to page 60
- ÖLFLEX® CLASSIC 100 BK 0,6/1 kV refer to page 33

Accessories

- SKINTOP® CLICK refer to page 687
- Detectable Cable ties refer to page 1042
- TY - FAST® cable ties refer to page 1041
- STAR STRIP stripping tool refer to page 985



Info

- CPR: Article number choice under www.lappkabel.com/cpr
- For nominal voltage U₀/U: 300/500V and conductor cross-sections below 2,5mm² see ÖLFLEX® CLASSIC 100 300/500V

Technical data

- Classification ETIM 5/6**
ETIM 5.0/6.0 Class-ID: EC001578
ETIM 5.0/6.0 Class-Description:
Flexible cable
- Core identification code**
Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9
From 6 cores: ÖLFLEX® colour code, refer to Appendix T7
- Conductor stranding**
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Torsion movement in WTG**
TW-0 & TW-1, refer to Appendix T0
- Minimum bending radius**
Occasional flexing: 15 x outer diameter
Fixed installation: 4 x outer diameter
- Nominal voltage**
U₀/U: 450/750 VAC
In protected and fixed installations:
U₀/U: 600/1000 V
- Test voltage**
4000 V
- Protective conductor**
G = with GN-YE protective conductor
X = without protective conductor
- Temperature range**
Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

ÖLFLEX® CLASSIC 100 450/750 V

Colour-coded PVC power and control cable



Benefits

- High electrical performance due to 4 kV test voltage
- High flexibility due to short-twisted conductor layers

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
Power stations
- Dry or damp rooms that are subject to medium mechanical loads
- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- PVC outer sheath, grey (similar RAL 7001)

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 450/750 V				
0010086	2 X 2,5	8.9	48	128
0010087	3 G 2,5	9.6	72	162
00100933	3 X 2,5	9.6	72	162
00100883	4 G 2,5	10.7	96	203
00100893	5 G 2,5	11.8	120	242
0010091	7 G 2,5	13.1	168	321
0010092	8 G 2,5	15.8	192	385
0010100	2 X 4	10.4	76.8	187
0010210	3 G 4	11.2	115.2	244
00101013	4 G 4	12.5	154	297
00101023	5 G 4	13.7	192	355
0010103	7 G 4	15.2	269	471
0010105	3 G 6	12.6	173	318
00101063	4 G 6	13.8	230	394
00101073	5 G 6	15.6	288	489
0010108	7 G 6	17.3	403	651
0010301	3 G 10	15.9	288	516
00101093	4 G 10	17.6	384	650
00101103	5 G 10	19.7	480	792
0010111	7 G 10	21.7	672	1058
0010302	3 G 16	18.3	461	728

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
00101123	4 G 16	20.4	614	1087
00101133	5 G 16	22.8	768	1118
0010303	3 G 25	23.0	720	1388
00101153	4 G 25	25.4	960	1582
00101163	5 G 25	28.5	1200	1771
0010304	3 G 35	25.6	1008	1766
00101173	4 G 35	28.5	1344	2106
00101183	5 G 35	31.9	1680	2635
0010305	3 G 50	31.0	1440	2556
00101193	4 G 50	34.5	1920	2943
00103133	5 G 50	38.6	2400	3936
0010306	3 G 70	35.3	2016	3182
00101203	4 G 70	39.4	2688	4092
00103143	5 G 70	44.1	3360	4800
0010307	3 G 95	41.3	2736	4675
00101213	4 G 95	45.8	3648	5290
00103153	5 G 95	51.6	4560	5600
0010308	3 G 120	47.6	3456	5626
00103093	4 G 120	53.1	4608	6994
00103113	4 G 150	57.4	5760	7500
00103123	4 G 185	62.8	7104	8300

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Single lengths for sizes: ≤ 5G50 max. 500 m; ≥ 5G95 max. 400; ≥ 3G120 max. 500 m; ≥ 4G120 max. 300; ≥ 4G185 max. 250 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC 100 300/500 V refer to page 27
- ÖLFLEX® CLASSIC 100 H refer to page 60
- ÖLFLEX® CLASSIC 100 BK 0,6/1 kV refer to page 33

Accessories

- SKINTOP® CLICK refer to page 687
- Detectable Cable ties refer to page 1042
- TY - FAST® cable ties refer to page 1041
- STAR STRIP stripping tool refer to page 985



ÖLFLEX® CLASSIC 100 YELLOW

Yellow outer sheath for special warning purposes



Info

- CPR: Article number choice under www.lappkabel.com/cpr
- For warning purposes

Benefits

- High electrical performance due to 4 kV test voltage

Application range

- For electrical circuits that remain 'live' after the main switch has been disconnected
- Service sockets and illumination circuits in electrical switchboards and cabinets
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Outer sheath: PVC, yellow (similar to RAL 1016)

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC001578 ETIM 5.0/6.0 Class-Description: Flexible cable
	Core identification code VDE 0293-308, refer to Appendix T9
	Conductor stranding Fine wire according to VDE 0295, class 5/IEC 60228 class 5
	Torsion movement in WTG TW-0 & TW-1, refer to Appendix T0
	Minimum bending radius Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
	Nominal voltage U0/U: 450/750 VAC In protected and fixed installations: U0/U: 600/1000 V
	Test voltage 4000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 YELLOW; U0/U: 450/750 V				
0010400	3 G 1.5	8.1	43	95
00104023	4 G 1.5	8.9	58	117
00104033	5 G 1.5	10.0	72	144
0010401	3 G 2.5	9.6	72	152
00104043	4 G 2.5	10.7	96	205
00104053	5 G 2.5	11.8	120	225

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® 450 P refer to page 80
- ÖLFLEX® 540 P refer to page 82

Accessories

- SKINTOP® CLICK refer to page 687
- STAR STRIP stripping tool refer to page 985



Info

- CPR: Article number choice under www.lappkabel.com/cpr
- EMC-compliant

ÖLFLEX® CLASSIC 100 CY

Colour-coded and screened PVC control cable



Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC001578 ETIM 5.0/6.0 Class-Description: Flexible cable
	Core identification code Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: ÖLFLEX® colour code, refer to Appendix T7
	Conductor stranding Fine wire according to VDE 0295, class 5/IEC 60228 class 5
	Minimum bending radius Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter
	Nominal voltage Up to 1.0 mm²: U0/U: 300/500 V From 1.5 mm²: U0/U: 450/750 V Fixed, protected installation: U0/U: 600/1000 V
	Test voltage 4000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C

Benefits

- Space-saving installation due to small cable diameters
- High electrical performance due to 4 kV test voltage

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Conveyor and transport systems
- Servo drives
- In EMC-sensitive environments (electromagnetic compatibility)

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1
- High degree of screening
low transfer impedance
(max. 250 Ω/km at 30 MHz)

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- PVC inner sheath, grey
- Tinned-copper braiding
- PVC outer sheath, transparent

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 CY; U0/U: 300/500 V				
0035001	2 X 0,5	7.0	41	75
0035002	3 G 0,5	7.3	46	83
00350033	4 G 0,5	7.9	55	99
00352013	5 G 0,5	8.4	66	112
0035202	7 G 0,5	8.9	80	132
0035004	2 X 0,75	7.4	46	86
0035005	3 G 0,75	7.9	57	100
00350063	4 G 0,75	8.4	64	115
00350163	5 G 0,75	8.9	77	130
0035203	7 G 0,75	9.7	102	161
0035220	2 X 1,0	7.9	56	98
0035221	3 G 1,0	8.2	65	111
00352223	4 G 1,0	8.7	78	130
00352233	5 G 1,0	9.5	89	153
0035204	7 G 1,0	10.2	113	185
ÖLFLEX® CLASSIC 100 CY; U0/U: 450/750 V				
0035000	2 X 1,5	9.9	65	132
0035458	3 G 1,5	10.3	79	170
00354593	4 G 1,5	11.3	97	204
00354603	5 G 1,5	12.6	116	246
0035461	7 G 1,5	13.9	149	320
0035011	3 G 2,5	11.8	146	211
00350173	4 G 2,5	13.5	167	310
00350123	5 G 2,5	14.6	200	326

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0035289	7 G 2,5	15.9	288	444
00350183	4 G 4	15.1	237	403
00350133	5 G 4	16.5	328	478
00350193	4 G 6	16.6	318	521
00350143	5 G 6	18.2	441	624
0034953	3 G 10	18.9	414	690
00350213	4 G 10	21.1	558	843
00352903	5 G 10	23.1	714	1004
0034954	3 G 16	21.7	607	910
00350223	4 G 16	23.9	804	1164
00350153	5 G 16	26.8	1050	1812
0034955	3 G 25	26.6	936	1330
00350233	4 G 25	29.4	1289	1903
00350243	5 G 25	32.6	1446	2374
0034956	3 G 35	29.4	1258	1370
00350253	4 G 35	32.4	1693	2489
00350263	5 G 35	36.0	1975	2771
0034952	3 G 50	35.1	1748	2590
00350273	4 G 50	38.8	2342	3362
00350283	4 G 70	43.7	3035	3719
00350293	4 G 95	50.4	4055	5849
00354303	4 G 120	56.8	5225	7509
00354313	4 G 150	62.2	6300	7800
00354323	4 G 185	67.8	7753	9866

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Single lengths for sizes: ≥ 4G50 max. 500 m; ≥ 4G95 max. 400 m; ≥ 4G120 max. 300 m; ≥ 4G150 max. 250 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® SERVO 9YSLCY-JB refer to page 98
- ÖLFLEX® SERVO 2YSLCY-JB refer to page 97

Accessories

- SKINTOP® BRUSH ADD-ON refer to page 700
- 3M Scotch™ 1183 screening tape refer to page 1030
- SKINTOP® MS-HF-M BRUSH refer to page 708
- SKINTOP® MS-M BRUSH refer to page 702



ÖLFLEX® CLASSIC 100 SY

Colour-coded PVC control cable with steel wire braiding



Benefits

- Extra mechanical protection due to braided steel wire

Application range

- Plant engineering
- Industrial machinery
- Heating and air-conditioning systems
- Areas with high mechanical stress

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- PVC inner sheath, grey
- Braid of galvanized steel wires
- PVC outer sheath, transparent

Info

- CPR: Article number choice under www.lappkabel.com/cpr
- Steel wire braiding for extra mechanical protection

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC001578 ETIM 5.0/6.0 Class-Description: Flexible cable
	Core identification code Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: ÖLFLEX® colour code, refer to Appendix T7
	Conductor stranding Fine wire according to VDE 0295, class 5/IEC 60228 class 5
	Minimum bending radius Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter
	Nominal voltage Up to 1.5 mm²: U0/U: 300/500 V From 2.5 mm²: U0/U: 450/750 V From 2.5 mm², in the case of fixed and protected installations: U0/U: 600/1000 V
	Test voltage 4000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 SY; U0/U: 300/500 V				
0016022	2 X 0,75	8.2	14.4	97
0016023	3 G 0,75	8.5	21.6	108
00160243	4 G 0,75	9.2	28.8	126
00160253	5 G 0,75	9.7	36	146
0016027	7 G 0,75	10.3	50	172
0016031	12 G 0,75	12.9	86	260
0016042	2 X 1,0	8.5	19.2	137
0016043	3 G 1,0	8.8	29	154
00160443	4 G 1,0	9.5	38.4	180
00160453	5 G 1,0	10.1	48	202
0016047	7 G 1,0	11.0	67	242
0016064	2 X 1,5	9.3	29	172
0016065	3 G 1,5	9.7	43	191
00160663	4 G 1,5	10.2	58	217
00160673	5 G 1,5	11.1	72	268
0016069	7 G 1,5	11.9	101	311
0016072	12 G 1,5	15.4	173	499
0016075	18 G 1,5	17.6	259	652
0016077	25 G 1,5	20.3	360	913

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 SY; U0/U: 450/750 V				
0016087	2 X 2,5	12.1	48	245
0016088	3 G 2,5	12.6	72	278
00160893	4 G 2,5	13.9	96	339
00160903	5 G 2,5	15.2	120	397
0016092	7 G 2,5	16.3	168	470
0016101	2 X 4	13.6	76.8	329
00161023	4 G 4	15.7	154	457
00161033	5 G 4	17.1	192	545
0016106	3 G 6	15.8	173	544
00161073	4 G 6	17.2	230	687
00161083	5 G 6	18.8	288	798
00161103	4 G 10	21.3	384	1009
00161113	5 G 10	23.3	480	1197
00161133	4 G 16	24.1	614	1384
00161143	5 G 16	26.8	768	1740
00161163	4 G 25	29.4	960	2021
00161173	5 G 25	32.6	1200	2464
00161183	4 G 35	32.4	1344	2570
00161193	5 G 35	36.0	1680	3185
00161203	4 G 50	38.8	1920	3514

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Single lengths for sizes: ≥ 4G35 max. 500 m; ≥ 4G95 max. 400 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC 110 SY refer to page 42

Accessories

- Ratchet cutter refer to page 980
- KT cable shears

ÖLFLEX® CLASSIC 100 BK 0,6/1 kV

Info

- Good outdoor performance



Benefits

- High electrical performance due to 4 kV test voltage

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
Power stations
Stage applications
- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)
- Suitable for outdoor applications
- Each dimension with nominal/ minimum average wall thickness of the outer sheath of at least 1.8 mm: For applications where a strengthened outer sheath may turn out to be advantageous

Product features

- Flame-retardant according IEC 60332-1-2
- UV and weather-resistant according to ISO 4892-2
- Ozone-resistant according to EN 50396
- Flexible down to -30°C

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: PVC, cold-resistant
- PVC outer sheath, cold-resistant, black (RAL 9005)

Technical data

Classification ETIM 5/6
ETIM 5.0/6.0 Class-ID: EC000057
ETIM 5.0/6.0 Class-Description: Low voltage power cable

Core identification code
Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9
From 6 cores: ÖLFLEX® colour code, refer to Appendix T7

Conductor stranding
Fine wire according to VDE 0295, class 5/IEC 60228 class 5

Torsion movement in WTG
TW-0 & TW-1, refer to Appendix T0

Minimum bending radius
Occasional flexing: 15 x outer diameter
Fixed installation: 4 x outer diameter

Nominal voltage
U0/U: 600/1000 V

Test voltage
4000 V

Protective conductor
G = with GN-YE protective conductor
X = without protective conductor

Temperature range
Occasional flexing: -30°C to +70°C
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 BK 0,6/1 kV				
1120457	3 G 1,0	9.0	29	112
1120459	5 G 1,0	10.4	48	152
1120462	2 X 1,5	9.6	29	123
1120463	3 G 1,5	10.1	43	144
1120464	4 G 1,5	10.8	58	170
1120465	5 G 1,5	11.7	72	199
1120469	3 G 2,5	11.3	72	182
1120470	4 G 2,5	12.2	96	225
1120474	4 G 4	13.8	154	324
1120475	4 G 6	15.1	230	442

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Other sizes and screened types are available upon request.
Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC 130 H BK 0,6/1 kV refer to page 66
- ÖLFLEX® CLASSIC 110 BLACK 0,6/1 kV refer to page 43

Accessories

- FLEXIMARK® Stainless steel kit refer to page 963
- SKINTOP® MS-M refer to page 696
- SKINTOP® BS-M METAL / SKINTOP® BSR-M METAL refer to page 698



ÖLFLEX® SMART 108

Cost-effective VDE-registered PVC control cable

LAPP KABEL STUTTGART ÖLFLEX® SMART 108 VDE-Reg. Nr. 8639 CE



Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC000104 ETIM 5.0/6.0 Class-Description: Control cable
	Core identification code Black with white numbers acc. to VDE 0293-1
	Conductor stranding Fine wire according to DIN EN 60228 (VDE 0295), class 5 / IEC 60228 class 5
	Minimum bending radius Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
	Nominal voltage U0/U: 300/500 V
	Test voltage 4000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Occasional flexing: -5 °C to +70 °C Fixed installation: -40 °C to +80 °C

Benefits

- SMART: good price/performance ratio the ÖLFLEX® SMART 108 has everything a flexible control cable needs
- SMART: environmentally friendly internal sheath layer made from recycled PVC with the same high quality of the TM2 model

Application range

- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Dry or damp rooms that are subject to medium mechanical loads
- Main dimensions available, further dimensions see ÖLFLEX® CLASSIC 110
- For extended applications and individual lengths, see ÖLFLEX® CLASSIC 110

Info

- CPR: Article number choice under www.lappkabel.com/cpr
- VDE certificate of conformity with factory surveillance
- Only available in standard lengths and standard packagings

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1
- Oil resistance: see data sheet

Norm references / Approvals

- VDE reg. no. 8639

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation, TI2
- Two-layer PVC outer sheath, TM2; outside silvergrey

Article number	Number of cores and mm² per conductor	Standard length (m) and standard packaging						Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
		50 m / RG	100 m / RG	200 m / RG	200 m / DR	500 m / DR	1000 m / DR			
ÖLFLEX® SMART 108										
17520099	2 X0,5		100	200		500	1000	4.8	9.6	35
10030099	3 G0,5		100	200		500	1000	5.1	14.4	42
17530099	3 X0,5		100	200		500	1000	5.1	14.4	42
10040099	4 G0,5		100	200		500	1000	5.7	19.2	54
17540099	4 X0,5		100	200		500	1000	5.7	19.2	54
10050099	5 G0,5		100	200		500	1000	6.2	24	63
10070099	7 G0,5	50	100	200		500	1000	6.7	33.6	81
18020099	2 X0,75		100	200		500	1000	5.4	14.4	45
11030099	3 G0,75		100	200		500	1000	5.7	21.6	55
18030099	3 X0,75		100	200		500	1000	5.7	21.6	55
11040099	4 G0,75		100	200		500	1000	6.2	28.8	66
18040099	4 X0,75		100	200		500	1000	6.2	28.8	66
11050099	5 G0,75	50	100	200		500	1000	6.7	36	79
11070099	7 G0,75	50	100	200		500	1000	7.3	50	101
18520099	2 X1,0		100	200		500	1000	5.7	19.2	53
12030099	3 G1,0		100	200		500	1000	6.0	28.8	65
12040099	4 G1,0	50	100	200		500	1000	6.5	38.4	79
12050099	5 G1,0	50	100	200		500	1000	7.1	48	94
12070099	7 G1,0	50	100	200		500	1000	8.0	67	126
19020099	2 X1,5		100	200		500	1000	6.3	29	68
13030099	3 G1,5	50	100	200		500	1000	6.7	43	84
13040099	4 G1,5	50	100	200		500	1000	7.2	58	104
13050099	5 G1,5	50	100	200		500	1000	8.1	72	128
13070099	7 G1,5	50	100		200	500	1000	8.9	101	166
19520099	2 X2,5	50	100	200		500	1000	7.5	48	101
14030099	3 G2,5	50	100	200		500	1000	8.1	72	132
14040099	4 G2,5	50	100		200	500	1000	8.9	96	163
14050099	5 G2,5	50	100		200	500	1000	10.0	120	200
14070099	7 G2,5	50	100		200	500	1000	11.1	168	267

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Standard packaging: ring = RG, drum = DR

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC 110 refer to page 35
- ÖLFLEX® CLASSIC 110 BK refer to page 38

Accessories

- EPIC® Industrial connectors refer to page
- SKINTOP® ST-M refer to page 684
- SKINTOP® ST-M Small PU